

Changes the browser's URL to the normalized version of the given URL, and replaces the top item on the platform's history stack.

- `forward() : void`

Navigates forward in the platform's history.

- `back() : void`

Navigates back in the platform's history.

- `subscribe(onNext: (value: any) => void, onThrow?: (exception: any) => void, onReturn?: () => void) : Object`

Subscribe to the platform's popState events.

Example of location service

- `import {Component} from '@angular/core';`
- `import {Location} from '@angular/common';`
-
- `@Component({selector: 'app-component'})`
- `class AppCmp {`
- `constructor(location: Location) {`
- `location.go('/foo');`
- `}`
- `}`

The above code navigates the browser url to `<current>/foo` and adds it to platform history.

Compiler

The compiler service can be defined as a low-level service for running the angular compiler during runtime to create ComponentFactories, which can later be used to create and render a Component instance.

This allows components to be dynamically created at runtime leading to a richer application.

The two most commonly used methods of the compiler service are

- `compileModuleSync(moduleType: Type<T>) : NgModuleFactory<T>`

Compiles the given NgModule and all of its components.

- `compileModuleAsync(moduleType: Type<T>) : Promise<NgModuleFactory<T>>`

Compiles the given NgModule and all of its components asynchronously.

The compiler service is used extensively in applications where the components and more specifically templates for the components are