

Testing the TossService via Jasmine:

```

• import { addProviders, inject } from '@angular/core/
testing';
import { TossService } from './toss.service';

describe('TossServiceTest', () => {
  beforeEach(() => {
    addProviders([TossService]);
  });

  it('#coinFlip should return heads or tails',
  inject([TossService], (service: TossService) => {
    expect(service.coinFlip()).toMatch('(?:heads|tails)');
  }));
});

```

The above code can be used to easily write a test case to check the function `coinFlip` in the service `TossService`. The service is injected here before each test case is run and then the function `coinFlip` is called whose result is expected to match to one of the two words 'heads' or 'tails'.

As much as it might seem like a waste of crucial development hours it is imperative, that all services and their functions have their corresponding tests written since a disruption in a service would lead to catastrophic results for the entire angular application.

Often, in some cases we may need to test a functionality or a service that communicates with a backend server or uses an external resource that is either difficult to inject or not possible at all (pay per hit backend servers etc). In this case, the injectables are often mocked and their actual implementations ignored so that the services can be tested independently.

This decoupling of logic is perhaps one of the single most powerful feature of angular in general and services in particular.

Useful Links

- <http://dgit.in/LocStrgy>
- <http://dgit.in/TrnstmAPI>
- <http://dgit.in/GrpAPI>
- <http://dgit.in/SeqncAPI>
- <http://dgit.in/RouterAPI>
- <http://dgit.in/CompFctryAPI> 