

NgFor

<http://pastebin.com/edit/AD5LaiWq>

It is commonly used to process item of an iter-able objects and each markup outputting a markup. It can change DOM layout by removing and adding view DOM elements, thus, it is known as a Structural directive. It is very helpful for generating repeated content such as elements of drop-down or as list of customers, to name a few examples.

Each item processed has the following variables available:

Description	Variable
Example: <code>ngFor="#name of names"</code> . In this case the item has the variable 'name'.	Item itself
Current loop iteration for each template context.	Index
Boolean value indicating whether the item is the last one in the iteration	last
Boolean value indicating whether this item has an even index.	even
Boolean value indicating whether this item has an odd index.	odd

NgSwitch, NgSwitchWhen, NgSwitchDefault

<http://pastebin.com/edit/AD5LaiWq>

When matching of switch expression is required this directive is used for removing or adding DOM elements.

NgClass

<http://pastebin.com/edit/AD5LaiWq>

It is used to change appearance of DOM elements by removing or adding classes.

How to set one class with simple syntax :

- `<div [class]="classNames">Customer {{name}}.</div>`

Explanation:

1. Directive can be used in this manner.

- `<div *ngFor="#name of names">`
- `<div [ngClass]="{'selected': name == selectedName, 'unselected' : name != selectedName}"`
- `(click)="nameClicked($event)">{{name}}</div>`
- `</div>`