

```

•      <p>A in USD: {{a | currency:'USD':true}}</p>
•      <p>B in INR: {{b | currency:'INR':false:'4.2-2'}}</
p>`}}
•      export class CurrencyPipe {
•          a: number = 0.12345;
•          b: number = 1.09876;

```

LowerCasePipe & UpperCasePipe

The name says it all. These two pipes just change the cases of the characters in a string. They don't accept any parameters.

```

• import {Component, View} from 'angular2/core';
• @Component({selector: 'case-pipe',})
• @View({template: `
•     <h2>Lower and Upper case Pipe Example</h2>
•     <p>In lowerCase : {{str | lowercase}}</p>
•     <p>In uppercase : {{str | uppercase}}</p>`})
• export class LowerUpperCasePipe {
•     str: string = "My name is Paul Shan";

```

JSONPipe

Normally to refer to a value in a template we name it within double curly braces({{}}) which is called an expression, but this would not work on an entire object. In case we were to do this, we would end up something like [object object]. To print a JSON object properly we can use JSONPipe.

JSONPipe formats and outputs the object in a JSON format and displays it as part of the template. Of course, templating is just one aspect of it. JSONPipes are also useful to convert and view data that is coming from a remote server to ensure that the received json is a valid one and contains the required keys in it.

Another important use is in debugging, where it easily converts the required object to its string representation, so that we can know its state.

```

• import {Component, View} from 'angular2/core';
• @Component({selector: 'json-pipe',})
• @View({template: `
•     <h2>JSON Pipe Example</h2>
•     <h4>Without JSON Pipe</h4>
•     <pre>{{obj}}
•     <h4>With JSON Pipe</h4>
•     {{obj | json}}

```