

angular/*http*', shipped in a separate script file as part of the Angular npm package. We can import it from '@angular/*http*' because systemjs.config configured SystemJS to load that library when we need it.

Before we can use the Http client, we need to register it as a service provider with the dependency injection system. Let us begin by importing the necessary members. The newcomers are the *HttpModule* and the *JsonpModule* from the Angular HTTP library.

Following is a app.module.ts file contents in QuickStart project,
Code can be found here: <http://pastebin.com/FeqA7wNi>

First we are using typescript import statement to import *HttpModule* and *JsonpModule* in current file, after that we supply *HttpModule* and *JsonpModule* as part of the imports array in root NgModule App Module. Because we have told angular to import this modules on root module, Http functionality is available to all the module and components included in this project.

After registering *HttpModule* we are ready to use Angular Http client to make HTTP requests

Following are the APIs provided by Http class,
Code can be found here: <http://pastebin.com/XcULqAbD>

Each method takes in a url and a payload as the case may be and returns a generic observable response type.

Let's start with Http GET using following example,
Code can be found here: <http://pastebin.com/fCViX1uy>

First few lines in example imports required dependency classes. The Injectable decorator notifies angular that UserService has the dependency on other classes and they need to be provided at creation time. Http and Response classes provide interface to Angular HTTP functionality. The Observable class is imported from RxJS, it facilitates working with streaming data. In AngularJS 1 the ng.*IHttpService* (aka, *\$http*) was based on promises and deferrals, AngularJS 2 now rely on RxJS and the observable pattern. Read more about RxJS Observable at <http://dgit.in/ReactObs>.

The RxJS library is large. Size matters when building a production application and deploying it to mobile devices, hence Angular exposes a stripped down version of Observable in the rxjs/Observable module that lacks most of the operators such as the map. The two lines after