

```

•
• import { AppComponent } from './app.component';
•
• @NgModule({
•   imports: [
•     BrowserModule,
•     FormsModule,
•     HttpClientModule,
•     JsonpModule ],
•   declarations: [ AppComponent ],
•   bootstrap: [ AppComponent ])
•
• export class AppModule { }

```

Following is the method available on the `Jsonp` class,

```

• request(url: string|Request, options?: RequestOptions-
  sArgs) : Observable<Response>

```

First argument is required, and can either be a url or a `Request` instance. If the first argument is a url, an optional `RequestOptions` object can be provided as the 2nd argument.

Let's rewrite `getUsers` service using angular `Jsonp` functionality.

Code can be found here: <http://pastebin.com/vqKCz3DE>

We have changed the constructor dependency on `Jsonp` instead of `Http` class. `Jsonp.request()` method is used to make `Jsonp` request to server and retrieve users in the `JSON` format.

The `JSONP` technique requires that we pass a callback function name to the server in the query string: `callback=JSONP_CALLBACK`. The server uses that name to build a JavaScript wrapper function in its response, which Angular then calls to extract the data.

## Useful Links

- <http://dgit.in/httpAPIdoc>
- <http://dgit.in/ReqstClass>
- <http://dgit.in/RqstOptns> 