

The Angular framework, on the other hand, is targeted to develop a single page application or SPA. In SPA, the current page is not completely discarded, instead, the part of the page is replaced with the different content loaded dynamically using JavaScript and DOM manipulation. This technique gives a web application similar feel like that of the desktop application.

In Angular, we have a web page made up of multiple distinct parts, called view and depending on the business logic, such views are shown or hidden using the Angular Routing module. Basically, the Angular Router handles the navigation in Angular application.

The Angular router uses the same concept of URL navigation. It navigates to a different view or modified the currently displayed view depending upon the current URL of the web browser.

We can bind the router to links on a page and it will navigate to the appropriate application view when the user clicks a link. It can navigate to a different view when the user clicks a button, or selects from a drop box, or in response to some other input from any source. And the router logs activity in the browser's history journal so the back and forward buttons work as well.

The Router Basics(setting up the routes)

1. <base href>

The base tag should be the first child of head tag. It specifies the base URL of all relative URLs on the page. It is required by the router. If it is not possible to add base tag, an alternative would be to declare APP_BASE_HREF provider with custom value. For example,

```
• import {Component, NgModule} from '@angular/core';
• import {APP_BASE_HREF} from '@angular/common';
•
• @NgModule({
•   providers: [{provide: APP_BASE_HREF, useValue: '/base-
Path/'}]
• })
• class AppModule {}
```

The Router utilises the browser's history.pushState for the navigation. A <base href> element tag must be added to the index.html for the push-State routing to work. The base href value is also needed by the browser, when downloading and linking to css files, scripts, and images, to prefix relative URLs.