

- `matcher` defines a custom strategy for path matching and supersedes `path` and `pathMatch`.
- `component` is a component type.
- `redirectTo` is the url fragment which will replace the current matched segment.
- `outlet` is the name of the outlet the component should be placed into.
- `canActivate` is an array of DI tokens used to look up `CanActivate` handlers.
- `canActivateChild` is an array of DI tokens used to look up `CanActivateChild` handlers.
- `canDeactivate` is an array of DI tokens used to look up `CanDeactivate` handlers.
- `canLoad` is an array of DI tokens used to look up `CanDeactivate` handlers.
- `data` is additional data provided to the component via `ActivatedRoute`.
- `resolve` is a map of DI tokens used to look up data resolvers.
- `children` is an array of child route definitions.
- `loadChildren` is a reference to lazy loaded child routes.

To configure routes, we provide an array of route objects to `RouterModule.forRoot()` method and import them on application's root module, that is `AppModule`

Let's begin with the Angular QuickStart project. Here's the modified `app.module.ts`

Code can be found here: <http://pastebin.com/r1Hyf0ld>

We have added few required component for our example `HomeComponent`, `Screen1Component`, `Screen2Component` and `PageNotFoundComponent`.

An array `appRoutes` declares four path, each navigating to different component specified by "component" attribute. The empty path entry matches the empty path segment, which basically says to redirect to `HomeComponent` when no path is present. The `**` in the last route denotes a wildcard path for our route. The router will match this route if the URL requested doesn't match any paths for routes defined in our configuration. We import `RouterModule` by invoking method `RouterModule.forRoot(<routes>)` in imports segment of `NgModule` decorator.

The order of the routes in the configuration matters and this is by design. The router uses a first-match wins strategy when matching routes, so more specific routes should be placed above less specific routes.

We have no leading slashes in our path, which is a relative path from the parent component, ie `AppComponent`. We can specify absolute path by