

Following is the AppModule with the two routes,

```

• import { NgModule }      from '@angular/core';
• import { RouterModule, Routes } from '@angular/router';
• import { BrowserModule } from '@angular/platform-
browser';
• import { AppComponent }  from './app.component';
• import { AbcComponent }  from './abc.component';
• import { PageNotFoundComponent } from './page-not-found.
component';
•
• const appRoutes = [
•   { path: 'abc/:reqVar', component: AbcComponent },
•   { path: '**', component: PageNotFoundComponent }
• ];
•
• @NgModule({
•   imports:      [ BrowserModule, RouterModule.
forRoot(appRoutes) ],
•   declarations: [ AppComponent, AbcComponent, PageNot-
FoundComponent ],
•   bootstrap:    [ AppComponent ]
• })
• export class AppModule { }

```

Notice AbcComponent has “abc/:reqVar” path declared, here reqVar is variable name extracted with the contents of same place in url. We don't need to declare any optional paramter here.

Let us view the AppComponent code,

```

• import { Component } from '@angular/core';
•
• @Component({
•   selector: 'my-app',
•   template: `
•     <ul style="list-style: none;">
•       <li><a [routerLink]="['/abc']">reqVar = Nil, optVar =
Nil</a></li>
•       <li><a [routerLink]="['/abc/10']">reqVar = 10, optVar =
Nil</a></li>

```