

```

• <li><a [routerLink]="['\abc/20', { optVar: 30 }]">reqVar
= 20, optVar = 30</a></li>
• </ul> <hr>
• <router-outlet></router-outlet>
• `
• })
• export class AppComponent { }

```

AppComponent has declared three routerLink to AbcComponent, these links are combinations of reqVar and optVar with value present and value absent.

The AbcComponent is defined as follows,

Code can be found here: <http://pastebin.com/HZFQHua2>

There are few things new, first we have imported OnInit, OnDestroy from angular core and ActivateRoute from @angular/router. ActivatedRoute provides access to the route parameters, navigation history and the hierarchy of the components.

ngOnInit, ngOnDestroy functions provide hooks into the angular dependency life cycle. ngOnInit method is called once when the object is created and ngOnDestroy is called when object is discarded and is no longer used.

In ngOnInit we subscribe to the route parameter changes using subscribe method on route.params(). This subscription allows us to monitor route parameter changes and updates the local variable used in template. The subscriber must be discarded when is not needed otherwise we could have a memory leak in our application. We unsubscribe in the ngOnDestroy method.

Let's test the behaviour of our example,

If first link is clicked, which has not provided any parameters, the application displays page not found. We have a wildcard route defined to handle any non-existent route calls. This confirms that path segment parameters are required to match the route.

The second link provides the required parameter but does not pass the optional parameters, on click of second link, AbcComponent displays the required parameter value but optional parameter value is shown empty.

The third link provides both values and they are displayed correctly by AbcComponent.