

basic illustration. In the first place, we will inspect a “master” page format. Since most web applications keep up a similar general design across different pages, it’s helpful to characterise this format as a single Blade view:

```
<!-- Stored in resources/views/layouts/app.blade.php -->
<html>
  <head>
    <title>App Name - @yield('title')</title>
  </head>
  <body>
    @section('sidebar')
      This is the master sidebar.
    @show
    <div class="container">
      @yield('content')
    </div>
  </body>
</html>
```

This is quite similar to HTML language. The ‘@section’ directive is used to define the section of content. The ‘@yield’ directive is used to display the respective content of the section. This is the basic procedure for defining a layout. Blade follows the principles of inheritance. If we create a ‘child’, it would follow all the basic properties of the parent view. While defining a ‘child’ view, we use the ‘@extends’ directive to define which layout the child ‘inherits’ from. The contents are again displayed using the ‘@yield’ directive. Let us have a look how this is done:

```
<!-- Stored in resources/views/child.blade.php -->
@extends('layouts.app')
@section('title', 'Page Title')
@section('sidebar')
  @parent
  <p>This is appended to the master sidebar.</p>
@endsection
@section('content')
  <p>This is my body content.</p>
@endsection
```

The ‘sidebar’ section is being used here to append extra content to the layout’s sidebar without overwriting. When we render the view using ‘@yield’, the ‘@parent’ directive will be replaced by the content of this layout.