

Control structures

In addition to having template inheritance and display directives, we can also use control structures like if statements and loops with Blade. There are predefined shortcuts which provide a simple straightforward way of working with PHP control structures.

<i>compute the largest power of 2 less than or equal to n</i>	<pre>int power = 1; while (power <= n/2) power = 2*power; System.out.println(power);</pre>
<i>compute a finite sum (1 + 2 + ... + n)</i>	<pre>int sum = 0; for (int i = 1; i <= n; i++) sum += i; System.out.println(sum);</pre>
<i>compute a finite product (n! = 1 × 2 × ... × n)</i>	<pre>int product = 1; for (int i = 1; i <= n; i++) product *= i; System.out.println(product);</pre>
<i>print a table of function values</i>	<pre>for (int i = 0; i <= n; i++) System.out.println(i + " " + 2*Math.PI*i/n);</pre>
<i>compute the ruler function (see PROGRAM 1.2.1)</i>	<pre>String ruler = "1"; for (int i = 2; i <= n; i++) ruler = ruler + " " + i + " " + ruler; System.out.println(ruler);</pre>

An example of using loops to solve some basic problems

Localisation

Now let us talk about another special feature that laravel contains. Laravel has inbuilt support for multiple languages within the created application. It does this by providing a simple way of retrieving strings in various languages. The language strings are saved in the 'resource/lang' directory.

The default language for the application is always stored in the 'config/app.php' configuration file. A 'fallback language' may also be saved in case the active language does not contain any translation script. This is saved in the 'config/app.php' directory file. We can also define the different translation strings. The information for these strings is stored in the 'resources/lang' directory.

```
/resources
/lang
/en
```