

string of pagination links. You can easily convert results to JSON by using `toJson` method provided by the framework. The Laravel also provides several methods such as `count()`, `currentPage()`, `firstItem()`, `hasMorePages()`, `lastItem()`, `nextPageUrl()`, `perPage()`, `previousPageUrl()` and `total()`.

Migration

The main purpose of the migration is to enable developers to easily modify and share the overall database scheme of the application. They are paired with Laravel's schema builder for simplicity purposes. As a developer, you should make use of the Laravel Schema facade to create and manipulate tables. You can create a migration by using the `make:migration` Artisan command such as `php artisan make:migration create_users_table`. The migration will be done and the relevant file will be placed inside your `database/migrations` directory with a timestamp.

The `--table` and `--create` options can also be used to indicate the table name and also to indicate whether a new table will be created during the migration process. If you examine the migration class, it consists of two methods such as `up` and `down`. The `up()` method is used to add new tables, columns and indexes to your database. As the name indicates, the `down()` method is used to reverse the operations completed by the `up()` method.

The `php artisan migrate` command should be used to run all the pending migrations, which will show you a prompt for confirmation. If you use `--force` flag, then you can force migrations without a prompt. The purpose of the prompt is to avoid loss of data. In case if you change your mind after the migration, you can use the `php artisan migrate:rollback` command to undo the most recent migration. the framework also provides an ability to rollback a specific number of migrations by using the `--step` option such as `php artisan migrate:rollback --step=6`.

The `php artisan migrate:refresh` command will automatically roll back all the migrations and also run the `migrate` command in one go. However, this command recreates the database and hence should be used with caution. Meanwhile, the `migrate:fresh` command will drop all tables from the database and also execute the `migrate` command.

You can create a new database table and columns by using `create()` method and `table()` method on the Schema facade. Both methods accept two arguments such as name of the table followed by a Blueprint object used to define table or column. A new index can be created using the `unique()` method like - `$table->string('email')->unique();`. If you use the