

by setting the `$dateFormat` property, which evaluates how date attributes are stored in the database. It also determines the format when the model is under serialized state.

The relevant model will take advantage of the default database connection values. You can configure different connections by using the `$connection` property. The data can be fetched from the database model by using `foreach()` loop structure and by adding `echo` property. If you use the `all()` method included with the Eloquent, it will return all the values from the table. You can use the `get()` method to fetch the results by adding constraints to queries. If you use `all()` and `get()` methods, an instance of `Illuminate\Database\Eloquent\Collection` will be returned. Moreover, the Collection class includes a wide range of methods.

Eloquent ORM provides `chunk()` method, which is mainly used to process thousands of records. The method is designed to work in a way to save memory and resources while processing massive result sets. The `chunk()` method accepts two arguments such as number of records you would like to receive per chunk. The second argument is a closure that will be called for each chunk. The `cursor()` method is used to scan through the database records without consuming huge memory resources. The `find()` and `first()` methods can be used to retrieve a single record from the database. The `find()` also accepts an array of primary keys, which is used to return a collection of records.

If you are involved in programming, you should provide the required code for tackling exceptions, which will throw in case a model is not found. The `findOrFail()` and `firstOrFail()` methods are used to fetch data via the query. If data has not been retrieved, the system will throw `Illuminate\Database\Eloquent\ModelNotFoundException` and a 404 HTTP response is delivered if the exception is not caught. To return aggregates, you should use the `count`, `sum`, `max`, and other aggregate methods included with the query builder.

You can insert a new record by creating a new model instance, configuring attributes and calling the `save()` method. The same method can also be used to update models. During the updation process, the `updated_at` timestamp will also be modified automatically. It is also possible to perform update tasks in bulk by specifying the conditions inside the `where()` method and passing the required criteria inside the `update()` method.

While `firstOrCreate()` method is used to trace a database record based on the criteria, the `firstOrCreate()` method will not only locate a specific