

ChromeDriver by default. You should then update the driver method to establish connectivity with the specific URL and port of your choice such as <http://localhost:4444>.

To create a browser, you should call the `App\User, Tests\DuskTestCase, Laravel\Dusk\Chrome, Illuminate\Foundation\Testing\DatabaseMigrations` class and call the `browse()` method, which accepts a callback. If you would like to carry out the testing process using multiple browsers, you can create them by providing the relevant code for activation of multiple browsers in the callback signature of the `browse()` method. Alternatively, you can employ `resize()` and `maximize()` methods to adjust the size of the window and also to increase the size of the active browser window.



Browser testing in progress

To test authenticated pages, you can make use of the `loginAs()` method, which accepts a user ID or user model instance as arguments. According to Laravel, `DatabaseMigrations` trait should be used for database migrations instead of `RefreshDatabase` trait.

Working with Elements

If you would like to write effective tests, you need to use dusk selectors instead of CSS selectors. You just need to add a dusk attribute to the relevant HTML element such as button. After that, you can use the `@` prefix along with the dusk selector to call the element. You can use the `clickLink()` method on the browser instance to click a link and it interacts with jQuery. If the jQuery is not available, the dusk will automatically activate it in such a way that the library is available for the entire test duration. You can use the `value()` method to fetch the actual value of an element that matches