

Enter the following to initialize the repository:

- `cd ~/android/lineage`
- `repo init -u https://github.com/LineageOS/android.git -b cm-14.1`

Download the source code

To start the download of the source code to your computer, type the following:

- `repo sync`

You can always play around with the manifest file but you need to remember that the manifest file depends on what all components you have included with the ROM. For reference, LineageOS' default values are `-j 4` and `-c`. The `-j 4` part means that there will be four simultaneous threads/connections. If you experience problems syncing, you can lower this to `-j 3` or `-j 2`. On the other hand, `-c` will ask repo to pull in only the current branch instead of all branches that are available on GitHub.

Prepare the device-specific code

After the source downloads, ensure you're in the root of the source code (`cd ~/android/lineage`), then type:

- `source build/envsetup.sh`
- `breakfast onyx`

This will download your device's device specific configuration and kernel.

Extract proprietary blobs

Ensure your OnePlus X is connected to your computer via the USB cable, with ADB and root enabled, and that you are in the `~/android/lineage/device/oneplus/onyx` folder. Then run the `extract-files.sh` script:

NOTE

Don't download the wrong build or you might brick your device.

NOTE

This may take a while, depending on your internet speed. You should probably watch a movie or start reading a book.

TIP

Changes are made on a near daily basis with LineageOS and the AOSP project. The `repo sync` command is used to update the latest source code on your machine from LineageOS and Google official repositories.