

- `./extract-files.sh`

The blobs should be pulled into the `~/android/lineage/vendor/oneplus` folder. If you see “command not found” errors, `adb` may need to be placed in `~/bin`.

Turn on caching to speed up build

Make use of `ccache` if you want to speed up subsequent builds by running:

- `export USE_CCACHE=1`

and adding that line to your `~/bashrc` file. Then, specify the maximum amount of disk space you want `ccache` to use by typing this:

- `ccache -M 50G`

where 50G corresponds to 50 GB of cache. This needs to be run once. Anywhere from 25 GB-100 GB will result in very noticeably increased build speeds (for instance, a typical 1hr build time can be reduced to 20 min). If you’re only building for one device, 25 GB-50GB is fine. If you plan to build for several devices that do not share the same kernel source, aim for 75 GB-100 GB. This space will be permanently occupied on your drive, so take this into consideration. See more information about `ccache` on Google’s Android build environment initialization page.

You can also enable the optional cache compression. While this may involve a slight performance slowdown, it increases the number of files that fit in the cache. To enable it, run:

- `export CCACHE_COMPRESS=1`

or add that line to your `~/bashrc` file.

IMPORTANT

If any of the commands don’t work then ensure all required files have been extracted and placed in the correct directories. Maintaining structure is very important when building ROMs. When the command line interface throws an error, you should Google the same to know how to fix it.

NOTE

If you face issues with pushing a build from your machine to your phone then there is a chance that it requires your phone to be already running a Lineage OS build. Refer to the official documentation to know more.