



Angled adapters can be used for hard tubing if they can't be bent easily.

tubing and cause leakage. Since PETG is softer, it will be able to deal with minor bends and bumps.

Apart from these two, you will find hard tubing made of borosilicate glass, copper, brass and even carbon. Glass will be the most resistant to any form of damage from coolant and probably look the best. The only problem with these materials is they can't be bent or cut using household tools. Although there are adapter fittings to make it easier to use them, the higher cost and extra work might put a lot of builders off. If you're a beginner, as we mentioned go for soft tubing. With some experience, you should venture out to hard tubing.

Measurements

When dealing with tubing and fittings, being able to read the measurements properly and understanding how they affect other parts is essential. It will make your planning phase shorter and you will be able to deal with quick changes easily. In the beginning, the measurements will be daunting since they are presented in two system of units including the metric and imperial units. Usually, both the measurements will be listed on the product page. So, you don't really need to follow just one unit. There are four diameters offered for tubing marked with inner diameter (ID) and outer diameter (OD). The sizes include 10/13mm, 10/16mm, 12/16mm and 13/19mm in the metric system measured in millimetres. In the imperial system, the measurements are 3/8"-1/2", 3/8"-5/8", 7/16"-5/8" and 1/2"-3/4" in inches. The smaller measurement is for ID and the bigger one is for OD. When you're