

performance in your overall system. We'd recommend cleaning up your custom loop every six to seven months. Over time, you will start noticing residue forming in the water blocks and the tubing getting muddy. Sometimes, if you don't pick the appropriate coolant, you might even see algae forming in the loop. These are clear signs of your cooling system needing a deep clean. To avoid all of these nasty problems, we'll be going through the parts one by one, starting off with draining the system.

Draining the loop

Whether you're using soft or hard tubing, before cleaning, you must drain the liquid. Generally, when you're conducting a regular maintenance of your custom loop, you would be changing the coolant along with cleaning the rest of the system. This is to prevent any kind of leakage or damage that could occur with minor bumps to the chassis. If you're cleaning your system every six months then you can do with a normal flushing and changing of the fluid. However, if you've been procrastinating and finally got time to clean your loop after a year, you might have to do a deep cleaning.

When you're buying the parts for a custom loop, you should keep in mind that you will be cleaning draining the system at some point. And in order to drain the loop easily, you'll need a drain valve. If not, then you'll have to buy extra accessories to suck out the fluid from the reservoir and tubes which can be tasking. Having a drain valve means that you can simply turn the valve and the fluid will start pouring out. The only time a drain valve can be a problem is space constraint inside your case and aesthetics. If you're going to place the reservoir at the bottom of the case, there might not be enough space for the valve to fit. While planning your loop design, a big



T-splitter fittings can be used in reservoirs to use one end for drainage