



grabs the input from our player through the keyboard. The float variables `moveHorizontal` and `moveVertical` record the input from the horizontal and vertical axis, which are controlled by the keys on a keyboard. Our player game object uses a rigidbody and interacts with a physics engine. We will use this input to add forces to the rigidbody and move the player game object in the scene. To know more about how to apply forces to the rigidbody let's check the documentation. Type `Rigidbody` in to our script. Now select `rigidbody` and hold down the command key on the mac or the control key on the pc and type single quote. Again, this brings a page with a search term "`rigidbody`". We want to click on `Rigidbody`. This brings up the `rigidbody` page. If we want to apply force to our player game object we need to do something. So let's look at the functions available to the `rigidbody` class. We read the descriptions until we find the one we want, in this case let's choose `AddForce`. This adds a force to the rigidbody as a result the rigidbody will start moving. Click the link and we go to the page on `AddForce`. We can see the signature of the function at the top of the page. This signature tells us we need a `vector3` and an optional `ForceMode` to add force to our rigidbody. What is a `vector3`? In simple terms the `vector3` holds 3 decimal values in one container. This makes it easy for us to move around and use values for things like a force in 3D space, which requires a value for force on each of the X, Y and Z-axis. Or to describe a rotation which would also require a value for each of the X, Y and Z-axis. All of our documentation pages are linked together. If we were to click on