

```

• using UnityEngine;
•
• public class Example : MonoBehaviour
• {
•     // Destroy everything that enters the trigger
•     void OnTriggerEnter(Collider other)
•     {
•         Destroy(other.gameObject);
•     }
• }
•
• This is the code that you copied. You need to edit to
read like
•
• void OnTriggerEnter(Collider other)
• {
•     if (other.gameObject.CompareTag ("Pick Up"))
•     {
•         other.gameObject.SetActive (false);

```

The function `OnTriggerEnter` will be called by Unity when the player gameobject first touches a trigger collider. A reference to the touched trigger collider touched is given as the second argument and is called `Other`. With this code, when the player touches another trigger collider, that gameobject is destroyed. This means that all of the gameobjects components and children and their components are removed from the scene. In this case, instead of destroying it, the objects will be deactivated. So you can remove the `Destroy(other.gameObject)` code line. Since you want to deactivate another gameobject, through a collision action, type in `GameObject` and look up the Scripting reference.

A few points to note here are-

- **Tag-** tag allows you to identify the gameobject by comparing the tag value to a string. They must be declared in the Tags and Layers Panel before you can use them.
- **SetActive-** this will activate or deactivate a gameobject through code. This is the code equivalent of clicking the Active check box next to the Name field in the Inspector. Write the line `GameObject.SetActive (false)`. The false call will deactivate the object.