

```

referenceImage.imageName) {
    Vector3 position = UnityARMatrixOps.
GetPosition (arImageAnchor.transform);
    Quaternion rotation = UnityARMa-
trixOps.GetRotation (arImageAnchor.transform);
    imageAnchorGO =
Instantiate<GameObject> (prefabToGenerate, position, rota-
tion);
}
}
Shader "Custom/Mask" {
    SubShader {
        //In the Tags section, we define different properties
for the subshader.
        Tags {
            //The main geometry render in the Geometry Pass.
Changing the Geometry pass to -1, we make sure it renders
first.
            "Queue" = "Background"
            //The ZWrite On value turns on the render to
Z-buffer. It's needed for proper sorting of the rendered
passes.
            ZWrite On //We don't want to render the
colour pass; ColorMask 0 will do the trick.
            ColorMask 0 Pass {}
        }
    }
}
using System;
using System.Collections.Generic;
namespace UnityEngine.XR.iOS
{
    public class UnityARHitTestExample : MonoBehaviour
    {
        public Transform m_HitTransform;
        Animator animation;
        bool HitTestWithResultType (ARPoint point, ARHit-
TestResultType resultTypes)

```

Unity Configuration

```

{
    List hitResults = UnityARSessionNativeInter-
face.GetARSessionNativeInterface ().HitTest (point, result-
Types);
    if (hitResults.Count > 0) {

```