

- } }

Add the following code to render the final droid object in the environment SDK and move on to the settings tab to change the node properties for the object.

```

• class TranslatableNode : Node() {
•     var position: DroidPosition = DroidPosition.DOWN
•     fun pullUp() {
•         // If not moving up or already moved up, start
animation
•         if (position != DroidPosition.MOVING_UP && position != DroidPosition.UP) {
•             animatePullUp()
•         } }
•     private fun localPositionAnimator(vararg values: Any?): ObjectAnimator {
•         return ObjectAnimator().apply {
•             target = this@TranslatableNode
•             propertyName = "localPosition"
•             duration = 250
•             interpolator = LinearInterpolator()
•             setAutoCancel(true)
•             // * = Spread operator, this will pass N `Any?`
values instead of a single list `List<Any?>`
•             setObjectValues(*values)
•             // Always apply evaluator AFTER object values or
it will be overwritten by a default one
•             setEvaluator(VectorEvaluator())
•         } }

```

Example Evaluation By ARCore

```

•     private fun animatePullUp() {
•         // No matter where you start (i.e. start from .3
instead of 0F),
•         // you will always arrive at .4F
•         val low = Vector3(localPosition)
•         val high = Vector3(localPosition).apply { y = +.4F

```