

CLOUD MARKERS IN ARKIT

ARKit's current setup allows for cloud markers to be used only with the second version of the software and can be emulated by Google ARCode as well. This sample code will run through the basics of first creating objects in real time, then using ARKit to communicate those through different channels and then finally adding anchor tags to the elements that can be viewed by the device users that are connected.

```

• configuration.planeDetection = .horizontal
• func setUpSceneView() {
•     let configuration = ARWorldTrackingConfiguration()
•     configuration.planeDetection = .horizontal
•     sceneView.session.run(configuration)
•     sceneView.delegate = self
•     sceneView.debugOptions = [ARSCNDebugOptions.show-
FeaturePoints]
• }
• func renderer(_ renderer: SCNSceneRenderer, didAdd
node: SCNNode, for anchor: ARAnchor) {
•     guard let planeAnchor = anchor as? ARPlaneAnchor
else { return }
•     let width = CGFloat(planeAnchor.extent.x)
•     let height = CGFloat(planeAnchor.extent.z)
•     let plane = SCNPlane(width: width, height: height)
•     plane.materials.first?.diffuse.contents =
UIColor.transparentLightBlue
•     let planeNode = SCNNode(geometry: plane)
•     let x = CGFloat(planeAnchor.center.x)
•     let y = CGFloat(planeAnchor.center.y)
•     let z = CGFloat(planeAnchor.center.z)
•     planeNode.position = SCNVector3(x,y,z)
•     planeNode.eulerAngles.x = -.pi / 2
•
•     node.addChildNode(planeNode)
• }
•

```

ARKit 2 Capabilities For Marker Anchoring

```

• // 1
• guard let planeAnchor = anchor as? ARPlaneAnchor,

```