

```

•
• // 4. Calculate and set new model position and orientation.
• let f3t = simd_make_float3(t, t, t)
• planeNode.simdWorldPosition = simd_mix(animationInfo.initialModelPosition, animationInfo.finalModelPosition, f3t)
• planeNode.simdWorldOrientation = simd_slerp(animationInfo.initialModelOrientation, animationInfo.finalModelOrientation, t)
• }

```

Game Sharing Elements Through AR Markers in ARCore

```

• func refreshAnimationVariables(startTime: TimeInterval, initialPosition: float3, finalPosition: float3, initialOrientation: simd_quatf, finalOrientation: simd_quatf) {
•     let distance = simd_distance(initialPosition, finalPosition)
•     // Average speed of movement is 0.15 m/s.
•     let speed = Float(0.15)
•     // Total time is calculated as distance/speed. Min time is set to 0.1s and max is set to 2s.
•     let animationDuration = Double(min(max(0.1, distance/speed), 2))
•     // Store animation information for later usage.
•     animationInfo = AnimationInfo(startTime: startTime,
•                                     duration: animationDuration,
•                                     initialModelPosition: initialPosition,
•                                     finalModelPosition: finalPosition,
•                                     initialModelOrientation: initialOrientation,
•                                     finalModelOrientation: finalOrientation)
• }
•     sceneView.scene.rootNode.addChildNode(shipNode)
• }

```