



REST API FlowChart

false positives, false negatives, true positives and true negatives that the model generates.

These refer to type 1 and type 2 errors that functional models can produce. As the names imply, true positives and true negatives are observed when the system correctly predicts the output in the testing set to that in the testing set. False negatives and positives occur when this identification is failed.

Generate a confusion matrix or undergo a simple regularisation step (for fine-tuning the parameters of the model). The matrix will let users know how many times the model correctly predicts for new data and is a good measure of knowing more about the parameters that influence its performance.

Popular frameworks for developing APIs include Swagger, WADL and RAML. Ideally when programming, developers also create an API Contract that details how the API should be used.

TERMS TO REMEMBER

Optimiser:- This is usually a string name indicating the optimiser instance.

Weighted Metrics:- Shows the metric to be evaluated and weighted by sample_weight or class_weight during training and testing phases.

LossWeights:- Loss weights are an optional list or dictionary specifying scalar coefficients that help in reducing errors in the output.

Sample Weight Mode:- Adds a different sample weight or importance to certain features or inputs over others.

BatchSize:- Indicates the number of samples per gradient update.

Epochs:- An epoch is an iteration over the inputs and outputs. The system will continue to run until the epochs have been achieved.

ValidationSplit:- Tells the API how to split the data for validation testing. The validation data is selected from the last samples in the data provided before being shuffled and reorganised.