

computer into a zombie or a bot. A bot is a compromised computer which can further be used to perform internet-based attacks. A botnet is a collection of bots which can collectively create havoc by a denial of service attack or sending spam emails.

Practical Hacking

Metasploit is one of the most extensive hacking/penetration testing tools. It has so many capabilities that we will only be scratching the surface in this article. It can be used for vulnerability scanning with Nexpose, for port scanning with Nmap, and numerous other hacking capabilities with its countless auxiliary modules

Web delivery exploits are used to open a web server on the attack system and then generate a simple script command. This script will open a Meterpreter shell on the target when executed. The internet delivery exploits use PHP, Python, or Windows PowerShell scripts (we can choose depending on the OS of the targeted web server).

Getting the script on to the target machine can be tricky. We need to get physical access to the system or encompass the code into a seemingly harmless-looking object that the target will execute without suspicion.

We will be exploiting a UNIX system or Macintosh system in this tutorial. They both have built-in Python interpreters. On successfully pulling this off, we can have complete control of the system including reading or deleting any files on the system, keystroke logging, turning on the webcam and recording from the mike.

Let's get started.

Open a Terminal

The first step is to boot up Kali Linux and open a terminal window.

Starting Metasploit and Loading the Exploit

We can start Metasploit by entering the following command

- `Kali > msfconsole`

This should open the msfconsole like that below.

```
in Metasploit Pro -- learn more on http://rapid7.com/metasploit
=[ metasploit v4.11.4-2015071403 ]
+-- --=[ 1468 exploits - 840 auxiliary - 232 post ]
+-- --=[ 432 payloads - 37 encoders - 8 nops ]
+-- --=[ Free Metasploit Pro trial: http://r-7.co/trymsp ]
```