


Let's consider another website that is hosted on a shared hosting and a reverse lookup showing the list of websites under the same IP address. The best part is that this website will highlight the potential websites that are easy to break in in "Red" colour. These sites marked in red are the ones hackers can easily access to get access to shared hosting.

b. Dig command (Linux Terminal)

The Dig (Domain Information Groper) is a command-line tool to query Domain Name Server (DNS) name servers. Dig is a Linux based command and is available across Linux based systems. Dig command also works in a way to perform reverse IP lookup as it retrieves the IP addresses of a particular domain.

For example, let's take the GNU website (www.gnu.org). Using the dig command, let's first get the IP address of the domain name. By using the dig command, you can make a DNS query to retrieve the IP address.



```
$ dig +noall +answer www.gnu.org
www.gnu.org.      207  IN  CNAME  wildebeest.gnu.org.
wildebeest.gnu.org. 207  IN  A      209.51.188.148
```

Now that we have the IP address of gnu.org domain, with the -x option, it is very easy to perform a reverse DNS lookup. With the reverse lookup, you can get the IP address and the domain name of the website.



```
$ dig +noall +answer -x 209.51.188.148
148.188.51.209.in-addr.arpa. 86392 IN  CNAME  148.0-24.188.51.209.in-addr.arpa
148.0-24.188.51.209.in-addr.arpa. 292 IN  PTR    wildebeest.gnu.org.
```

Using the dig command (reverse lookup method), we have found out the domain name of the website. If there are multiple websites under a single IP address, it becomes very simple for hackers to attack the websites.

c. Search Engines

One of the easiest ways for ethical hackers to get the list of websites running under a single server is to use search engines on the internet. Most search engines provide excellent results.