

e. Hacker Target

Similar to the CMS, Hacker Target offers an online portal that ethical hackers can use to find the server address information and websites that share the same IP address. Let's take an example and list down the other websites that share the same IP address from the hosting provider.

The screenshot shows the Hacker Target website interface. At the top, there's a search bar with the URL 'www.planespotterschennai.com'. Below it, a green button says 'SET IP INFORMATION'. The main heading is 'Server IP Address Information for 50.63.202.63'. On the left, there's a magnifying glass icon over a document. To its right, the IP address '50.63.202.63' is listed, along with 'Provider: GoDaddy.com' and 'Country: United States'. On the right side, there's a section for 'IP Reputation Check' which shows a large green 'PASSED' status. Below this, several security checks are listed with green checkmarks: 'Google Safe Browsing: Suspicious Check', 'Adware CC', 'Dyland Blocklist', and 'Gore Tides Blocklist'. At the bottom, there's a section titled 'Virtual Hosts (websites) found to be sharing this IP Address'. It contains a table with columns for 'hostname', 'HTTP Headers', 'Page Links (HTTP)', 'Page Links (HTTPS)', and 'Whois'. The table lists several websites: '17play.club', '30gulfairmerrill.com', '30urms.com', '776accounts.com', and '833ukoa.com'.

SQL Injection

One of the most common hacking methods used by hackers is the SQL injection attack. Since most websites use Structured Query Language (SQL) to communicate with the database to create, update, retrieve, delete records to/from the database, the SQL database is used pretty much to store the user details and other critical information. Hackers normally place these SQL injections on the web requests from address bars, data entry fields and search fields.

With SQL injection, the attacker will inject a set of SQL commands on to a web form or a URL string into the web application. The attacker will expect the application to understand the input and execute, thereby expecting a response from the database connected with the web application.

The simplest way of SQL injection is to type the character ' (single quote) or type in `1 = 1` in the username or password field of a web application.

If the application does not validate the user input correctly and instead appends the entered string to an SQL command request to the