

Here are the ways website owners can keep their websites and network safe from DoS attacks:

- **Firewall** – Make sure your network has a firewall configuration that restricts the bandwidth usage only to authorized users within the network. Contact your network administrator and ask them to tighten up all the network configurations and set up the firewall policies to route network connection requests through the firewall. Make sure your network administrator is aware of the complete network configuration and the logic behind the implementation.

There is also another type of DoS attack called the Distributed Denial of Service (DDoS) attack. This is similar to DoS, but with DDoS, the attack is distributed from various sources on to a single server. It becomes very difficult for network administrators to identify the root cause of the attacks.

To avoid these DDoS attacks, administrators can:

- Use the `mod_evasive` Apache module that helps to take evasive action in case of DoS/DDoS attacks. This module maintains a dynamic table with the list of URLs that have been accessed through the IP addresses. If there are too many requests from the same IP address within a period, `mod_evasive` automatically blocks the IP address from sending further requests.
- Taking advantage of Cloudflare services. Cloudflare acts like a proxy server between the server and the users accessing the server. With the ability to store the content in the cache and deliver to users on demand, it reduces the number of requests to the web server.
- **Filtering** – Administrators can set up dedicated routers that can identify the connections from multiple sources and prevent them from slowing down the server.
- **Blackholing** – The network administrator can direct all traffic to a specific site to an IP address that never exists to protect the server from being hacked.

4. Malware and Phishing Attacks

Malwares are malicious software that damage the computer system and steal sensitive information. To stay away from malwares –

- **Software Updates** – Make sure all your software is up-to-date as most ransomware attacks have known to happen with operating sys-