

- [5] Wireshark is a free and open-source packet analyzer. It is used for network troubleshooting, analysis, software and communications protocol development, and education: <https://en.wikipedia.org/wiki/Wireshark>
- [6] Reaver implements a brute force attack against Wifi Protected Setup (WPS) registrar PINs in order to recover WPA/WPA2 passphrases, as described in this paper: <https://tools.kali.org/wireless-attacks/reaver>
- [7] A network packet is a formatted unit of data carried by a packet-switched network : https://en.wikipedia.org/wiki/Network_packet
- [8] A hash function is any function that can be used to map data of arbitrary size onto data of a fixed size: https://en.wikipedia.org/wiki/Hash_function
- [9] The 4-way handshake is the process of exchanging 4 messages between an access point (authenticator) and the client device (supplicant) to generate some encryption keys which can be used to encrypt actual data sent over Wireless medium: <http://www.wifi-professionals.com/2019/01/4-way-handshake>

Social engineering

- [1] A penetration test, colloquially known as a pen test, is an authorized simulated cyberattack on a computer system, performed to evaluate the security of the system: https://en.wikipedia.org/wiki/Penetration_test
- [2] The Metasploit Project is a computer security project that provides information about security vulnerabilities and aids in penetration testing and IDS signature development. It is owned by Boston, Massachusetts-based security company Rapid7: https://en.wikipedia.org/wiki/Metasploit_Project
- [3] Ruby on Rails, or Rails, is a server-side web application framework written in Ruby under the MIT License: https://en.wikipedia.org/wiki/Ruby_on_Rails
- [4] Cross-site scripting (XSS) is a type of computer security vulnerability typically found in web applications. XSS enables attackers to inject client-side scripts into web pages viewed by other users: https://en.wikipedia.org/wiki/Cross-site_scripting
- [5] Code injection is the exploitation of a computer bug that is caused by processing invalid data. Injection is used by an attacker to introduce (or “inject”) code into a vulnerable computer program and change the course of execution: https://en.wikipedia.org/wiki/Code_injection