

The first command which we have used above will identify the partition. The second command will write the bootloader to MBR and then only you will be able to quit the Grub shell.

Following the above steps very carefully you can exit the GRUB and your Linux system will get rebooted. Restoration will also be easy and you have easily fixed the issues which you might have been facing.

Installation of device drivers on Linux

If you have the authentic reference and most precise commands, the installation of device drivers on Linux is not that typical.

The most daunting issue one could possibly face is that it is tricky to install and configure the drivers. As Linux is an open-source operating system, there is no possible way to create a single solution guide because there are multiple Linux distribution variation. The device drivers in Linux are open-source by default and also integrated into the system which makes it clear that installing any driver which is not a part of the system is complicated. Before actually understanding the installation process let's pay attention to some other segments.

How to find the Linux drivers?

There are two possible ways to find the Linux drivers -

With the help of the command line

You can follow this method if you have accessibility to Shell without a graphic interface or user interface application is not supported by you. It can also be done by two possible methods-

- Using a repository and updating the entire package
- By downloading, compiling and building the entire package by oneself

With the help of the user interface

This can be used by the freshers or someone who has just started with Linux. There is another way to see the available drivers with the help of a wizard program. An additional driver option is also presented by Ubuntu.

Installation of proprietary driver

Proprietary drivers provide the closed-source platform and have to be maintained and written on their own. It also promotes no bundling up for the Linux distribution and enables them automatically. For instance, there is an