

Step 4: Preparing the code for release

- Remove log statements.
- Remove the android:debuggable attribute from your manifest file
- Set the android:versionCode attribute within the manifest tag in manifest.xml. Two necessary notes to remember: (1) This should be Associate in Nursing number that will increase with every unharness. (2) The Number is not displayed to the user
- Set the android:versionName attribute within the manifest tag in manifest.xml. This string is shown to users but has no defined purpose

Step 5: Building a release-ready APK File

The release-ready APK is usually totally different from the debug APK because it's signed with a certificate that's closely-held by the developer. This step is taken to confirm that updates to the app return from a verified source, i.e. a developer with access to the non-public key.

We recommend that you follow the following directions to create a signed APK

Below given are some necessary take-away points:

- Android Studio -> Build -> Generate Signed APK
- A Java Keystore (JKS) is a repository of public-private key pairs.
- You should sign all APKs with the same key pair.
- Losing key-pair consequencet you just won't be able to push updates to your app.

Step 6: Transfer APK

Go back to the Developer Console and click on Manage Releases. Then create a Production release and transfer your signed APK.

Continuous Delivery

The guide will inform you about the ways to integrate Fastlane, an open-source tool suite with the existing testing and continuous Integration(CI) workflows.

Local setup

It's advised that you just take a look at the building and read-ying method locally before moving your application to a cloud-based system. You'll conjointly opt to execute continuous delivery from a neighborhood machine.