

ment board for their NRF52 SOC series. The NRF52 SOC is an ultralow energy, next-generation Bluetooth enabled single chip. The NRF52-DK development board is designed for low energy Bluetooth, ANT, and 2.4 GHz wireless applications. Additionally, the device also has a connector for RF measurements and also a pluggable NFC antenna to enable NFC tag functionality.

The key of this excellent development lies in its design which facilitates easy access to the I/O and interfaces via connectors and comes with 4 user-programmable LEDs plus as many programmable buttons.

Keeping the best for the last, the technicians at Nordic Semiconductors have designed the NRF52-DK in such a way that it is perfectly compatible with Arduino Uno R3. This



<https://cdn11.bigcommerce.com>

means the much revered third party Arduino shields can easily be linked to the NRF52-DK for performing different functions.

Highlight Features

Some of the highlights of NRF52-DK that make it stand out in the crowd are mentioned below:

- Bluetooth v4.2 compliant
- 2.4GHz multiprotocol radio
- On-chip NFC tag and ARM Cortex-M4F processor on a single chip optimised for ultra-low power operation
- Arduino Uno Rev. 3 compatible connector for use with 3rd party shields
- All I/O and interfaces available through connectors
- USB drag and drop programming plus USB Virtual COM port for serial terminal
- Segger J-Link and CMSIS-DAP interface for programming and debugging from offline tools and pyOCD
- Pluggable NFC antenna
- Connector for RF measurements
- Pins for power consumption measurements