

- When we send a query, the MySQL subsequently sends this to the server for further execution and returns the results on the same screen. Simultaneously prints `mysql>` to show that it is ready for the next query.
- MySQL provides display output in a tabular form with rows and columns. The first row has the labels for columns and then the results are followed thereafter from the second query.
- MySQL will provide information about the result with a specific number of rows returned and time is taken by the query to execute.
- Queries can be used single-line statements or multiple-line statements with semicolon in between.
- Long queries with one semicolon at the end of multiple-lines will have a similar performance.
- Using right notation you can use MySQL queries as a simple calculator too.
- Queries are not case-sensitive or not at all affected by any letter-case. So the below queries will give same results:

```
mysql> Select VERSION(), CURRENT_DATE;
mysql> select version(), current_date;
mysql> SElect vErSiOn(), current_DATE;
```

MySQL Create Statement and Create Database

Create statements are used for both Databases and tables respectively.

Create Database statement is used to create specific databases with a given name. You must add CREATE privilege for the Database to use this statement effectively. MySQL has no specific limits for the number of databases.

```
CREATE {DATABASE | SCHEMA} [IF NOT EXISTS] database_name
    [create_specification] ...
create_specification:
    [DEFAULT] CHARACTER SET [=] charset_name
    [DEFAULT] COLLATE [=] collation_name
```

Parameters:

`database_name`: particular name given to any specific database

`create_specification`: the options to specify any databases characteristics

CHARACTER SET: provides the default database character set

Example

In the given query we are creating a new database with a new chipmunk.

```
CREATE DATABASE chipmunk;
```

Similarly we can have various configurations to this database.