

```

BUFFER_RESULT ]
    [ SQL_CACHE | SQL_NO_CACHE ]
    [ SQL_CALC_FOUND_ROWS ]
expressions
FROM tables
[WHERE conditions]
[GROUP BY expressions]
[HAVING condition]
[ORDER BY expression [ ASC | DESC ]]
[LIMIT [offset_value] number_rows | LIMIT number_rows
OFFSET offset_value]
[PROCEDURE procedure_name]
[INTO [ OUTFILE 'file_name' options
      | DUMPFILE 'file_name'
      | @variable1, @variable2, ... @variable_n]
[FOR UPDATE | LOCK IN SHARE MODE];

```

Parameters:

- ALL: Optional and if included take a return from all matching rows.
- DISTINCT: Optional and if included removes duplicates from the set.
- DISTINCTROW: Optional and works as same as DISTINCT.
- HIGH_PRIORITY: Though optional, but if included, it makes the SELECT command priority to run before going for UPDATE statements.
- STRAIGHT_JOIN: Though Optional, but if included, it asks to join two tables in a specific order being listed in the FROM clause.
- SQL_SMALL_RESULT: Though optional, if provided, it uses fast temporary tables to store specific results.
- SQL_BIG_RESULT: Though optional, if provided, it uses sorting to store results in a table rather than a temporary table.
- SQL_BUFFER_RESULT: Uses a temporary table to store results (optional).
- SQL_CACHE: Though optional, if provided, it uses the results in a specific query cache.
- SQL_NO_CACHE: Though optional, if provided, it doesn't store the results in a query cache.
- SQL_CALC_FOUND_ROWS: Though optional, if provided, it calculates records in a given set that can be retrieved using the specific FOUND_ROWS.
- expressions: Main columns or the calculations that wish to retrieve in a given statement.