

**Parameters:**

- **LOW\_PRIORITY:** Optional, if provided, this update process will be delayed until no processes are reading from the table.
- **IGNORE:** Optional, if provided it will ignore all errors encountered during the update process.
- **column1, column2:** Name of the column that you want to update in the statement.
- **expression1, expression2:** New values that must replace the old values.
- **WHERE conditions:** An optional parameter though given it should be considered for updating the records to match it precisely.
- **ORDER BY expression:** Though optional, this is used in combination with **LIMIT** to sort the records to limit the number of the records in a given table.
- **LIMIT number\_rows:** Though optional, if provided this controls the maximum number for records to be updated in a given table.

In the following example, we are updating the last\_name to Merkel for the customer\_id is 3234.

```
UPDATE customers
SET last_name = 'Merkel'
WHERE customer_id = 3234;
```

Similarly to update multiple columns you can add multiple changes in values by separating them by commas.

```
UPDATE customers
SET state = 'London',
    customer_rep = 24
WHERE customer_id > 60;
```

The following query will update the state to London and customer\_rep to 24 when the customer\_id is greater than 60 respectively.

## MySQL Aggregate Functions

These are specific functions to perform calculations in MySQL. In this section, we will study these functions with their syntax parameters and examples.

```
MySQL MAX() Function
MySQL MIN() Function
MySQL COUNT() Function
MySQL SUM() Function
MySQL AVG() Function
```