

Example:

```
SELECT MIN (work_hour) AS "workMin"
FROM employees
[WHERE conditions];
```

MySQL MAX() Function

The MAX() Function in MySQL, is used to specifically return the maximum value of a given column.

```
SELECT MAX (column_name)
FROM table_name
[WHERE conditions];
```

Parameters:

- **column_name:** Column name from which the maximum value needs to be retrieved.
- **table_name:** Table name inside the database to retrieve values
- **WHERE conditions:** Optional values but if added needs to be matched

Example:

```
SELECT MAX (work_hour) AS "workMax"
FROM employees
[WHERE conditions];
```

Comparison Functions and LOGICAL Operators

In MySQL, Logical Operators have specific values with TRUE, FALSE or NULL(Unknown). Values are combined with one or more false or true values to come up for a specific solution. These values are represented as 1(TRUE), 0(FALSE), and NULL. These are followed by all SQL database servers, though few servers may return any specific nonzero values to be TRUE as well.

Main Logic Operators are:

OPERATOR	DESCRIPTION
AND (&&)	Logical AND – MySQL AND compares two Boolean expressions and then returns True when both the expression are true.
OR ()	Logical OR - MySQL OR operator compares two Boolean expressions and then returns true when either of the expression is TRUE.
NOT (!)	Logical NOT – MySQL NOT operator takes any single Boolean expression and then negates or reverses its value from TRUE to FALSE or FALSE to TRUE.