

```
+-----+
| this is case one |
+-----+
1 row in set (0.00 sec)
```

MySQL IN() Function

In the MySQL IN(), Function is used to find a match inside a given argument.

```
expr IN (value, ...)
```

MySQL IN() function will return 1 if the expr is exactly equal to the given values, otherwise, it will return 0. For constant values, Binary Search is used. In the following example, we are going to examine the functionality of MySQL IN function. The query asks for 4 to be found inside the match and will return 1 as TRUE.

```
SELECT 4 IN (2, 4, 8);
```

Output Statements will be:

```
mysql> SELECT 4 IN (2, 4, 8);
```

```
+-----+
| 4 IN (2, 4, 8) |
+-----+
| 1 |
+-----+
1 row in set (0.00 sec)
```

MySQL NOT Operator/Condition

This MySQL NOT Operator or Condition reverses or negates the condition in any of the Select, insert, update or Delete statements or condition.

Syntax: NOT

Note: MySQL NOT operator requires at least the opposite condition to have some match to get the desired result from a given set. Most of the time they are used in combination with other conditions. Here are a few examples.

NOT IN Condition Example

Here is an example of NOT with IN Condition with code.

```
SELECT *
FROM contacts
WHERE first_name NOT IN ('Rick', 'Mick', 'Tick');
```

The following query will return all rows from the contacts list table where the first name is not Rick, Mick, or Tick.