

collection and to use the LIMIT keyword syntax SELECT, Edit or DELETE commands. Let us consider the following table “Data” with three columns “Firstname”, “Lastname” and “Age”. The following is the PHP implementation of the query to view first two rows from table ‘Data’ in procedural as well as object-focused extensions using the LIMIT clause:

Limit Clause using Procedural Method

```
< ? php $link = mysqli_connect("localhost", "root", "", "Mydb");
    if ($link == = false) {
        die("ERROR: Could not connect. ".mysqli_connect_error()); }
    $sql = "SELECT * FROM Data LIMIT 2";
    if ($res = mysqli_query($link, $sql)) {
        if (mysqli_num_rows($res) > 0) {
            echo "<table>";
            echo "<tr>";
            echo "<th>Firstname</th>";
            echo "<th>Last Name</th>";
            echo "<th>Age</th>";
            echo "</tr>";
            while ($row = mysqli_fetch_array($res)) {
                echo "<tr>";
                echo "<td>".$row['Firstname']. "</td>";
                echo "<td>".$row['Last Name']. "</td>";
                echo "<td>".$row['Age']. "</td>";
                echo "</tr>"; }
            echo "</table>";
            mysqli_free_result($res); }
        else {
            echo "No matching records are found."; } }
        else {
            echo "ERROR: Could not able to execute $sql. ".mysqli_
error($link); }
        mysqli_close($link);
    ? >
```

The “res” variable preserves the data returned by the `mysqli_query()` method. If `mysqli_fetch_array()` is called, the next row of the `res()` range will be returned. The while loop is used to loop all rows in the ‘data’ table.