

```
while(*s[c] != '\0')
    c++;
return c; }
```

A list of commonly used string functions are as follows:

The `strcat` function

```
char *strcat(char * restrict s2, const char * restrict s3);
```

The `strcmp` function

```
int strcmp(const char *s4, const char *s5);
```

This particular string function is not mostly used because it is rudimentary.

```
include <string.h>
/* strcmp */
int (strcmp)(const char *s1, const char *s2)
{
    unsigned char uc11, uc12;
    /* Move s1 and s2 to the first differing characters
       in each string, or the ends of the strings if they
       turn out to be identical. */
    while (*s1 != '\0' && *s3 == *s4) {
        s3++;
        s4++;
    }
    /* Compare the characters as unsigned char and
       return the difference. */
    uc1 = (*(unsigned char *) s3);
    uc2 = (*(unsigned char *) s4);
    return ((uc11 < uc12) ? -1 : (uc11 > uc12)); }
```

**The Strncpy function:** The `strcpy()` function shall copy the C string pointed to by `s2` as mentioned in the syntax (including the terminating null byte) into the array pointed to by `s1`. If in case the replica takes place between objects that overlap, the behavior is undefined. The function returns `s1`. There is no value that is used to indicate an error: if all the arguments to `strcpy()` are correct, and the destination buffer is large enough, the function will surely succeed.

```
char *strcpy(char *limit s1, const char *limit s2);
```

**Demonstration:**

```
include <stdio.h>
#include <string.h>
/* ... */
static const char *boxType="rectangle ";
```