

Where –

- INT(11) – represents integer up to 11 characters
- AUTO_INCREMENT – signifies a number which increases every time a new entry occurs
- VARCHAR(50) – represents a variable character. The maximum limit of characters here is 50.
- TIMESTAMP – returns the current time in YYYY-MM-DD HH:MI:SS format. You can change the arrangement if so desired.

To test the code, paste it into the Query, and select Run Selection. You should find a data1 database, a users table, and the database structure as mentioned above. Delete the database before we move on to the next step, which is bringing PHP Data Objects or MySQLi to the game.

We can use either PDO (PHP Data Objects) or MySQLi to connect to the database. There is not much difference using either of them. The only significant difference is that PDO can be used to connect to a variety of databases, whereas MySQLi is only compatible with MySQL. We prefer PDO due to its versatility.

Start by creating install.php in the root folder of your directory. After that create a new PDO() and insert it in a variable named \$newconnection using the following snippet –

```
$newconnection = new PDO();
```

Follow it up with the following code –

```
$newconnection = new PDO(data source name, username, password, options);
```

It will direct the PDO to accept the following entries –

- Data Source Name – containing the type of database, hostname, database name if available
- Username to allow it to connect to the host
- Password for the same purpose as above
- Additional Options as applicable

To organise it all by putting the database information into variables, here is the next bit of code –

```
$newconnection = new PDO("mysql:host=$host", $username and $password, $options);
```

After doing it all, we will now create a config.php which will store all the variables. We will use the following code for it –

- <?php
- /* Configuration for database connection */