

- `<?php } } ?>`
- `<h2>Find user based on location</h2>`
- `<form method="post">`
- `<label for="location">Location</label>`
- `<input type="text" id="location" name="location">`
- `<input type="submit" name="submit" value="View Results">`
- `</form>`
- `<a href="index.php">Back to home</a>`
- `<?php require "templates/footer.php"; ?>`

Part 5 – Creating an Editable List

In this part, we are shifting to the third CRUD function, the update function. For this, we will create `update.php` and then add a link to it in `index.php`.

- `<?php include "templates/header.php"; ?>`
- `<ul><li><a href="create.php"><strong>Create</strong></a> - add a user</li>`
- `<li><a href="read.php"><strong>Read</strong></a> - find a user</li>`
- `<li><a href="update.php"><strong>Update</strong></a> - edit a user</li></ul>`
- `<?php include "templates/footer.php"; ?>`

Once done, we need to add an edit link for every user, which can be clicked upon to change any variables. The easiest way is to select all the users and then store them in another variable `$result`.

- `$sql = "SELECT * FROM users";`
- `$statement = $connection->prepare($sql);`
- `$statement->execute();`
- `$result = $statement->fetchAll();`

After that, build a try/catch block to list all the users with a link to edit. Here's the code a Google Doc (Section 1) – <https://digit.in/FTJan2020Code>

Part 6 – Modifying an existing entry

In the MySQL environment, it is easier to create a new entry than to edit an existing one. MySQL supports two types of modifiers in the update syntax –

- The `ignore` modifier which allows the syntax to update rows even if there is any error found. Any row where an error occurs is not updated at all.
- The `low_priority` modifier which asks the syntax to delay the update process until there is no connection-reading data from the table.