

Breakpoints

These are the special markers that are placed directly on the Blueprint Graph nodes. As the node marked with the breakpoint is about to be executed, the game gets paused and the viewer will see be shown the Blueprint Editor Graph views. Allowing them to check the values of each variable, data set or execution of the flow for a blueprint.

All the breakpoints specified in a Blueprints are shown in the Debug tab and are visible from the blueprint graph too when selected.

You can easily place a breakpoint on any given node by right-clicking the node and then selecting the Add breakpoint thereafter from the context menu. Once done a solid red octagon then will appear on the top left corner of the respective node. Similarly, you can also edit or remove the breakpoint by right-clicking and then selecting the Remove Breakpoint command.



Source: docs.unrealengine.com

These Breakpoints can also be created from the debug tab. These can be disabled, enabled, or then destroyed at any given point, including the debugging session. All the breakpoints are saved in a specific file named project.ini.

Breakpoints placed on invalid locations will appear yellow with an exclamation sign. Hold the mouse cursor over them to know the specific reason.

Debug Tab and Blueprint Debugger

All the information specified as important by the designer will be available in the Debug tab with breakpoints. You can easily watch values and check nodes for each blueprint with execution.

Watch Window

You can easily watch data from each of the Blueprints in the editor from the current call stack. This is collected into a single list being populated from the current data every time there is a pause for Blueprint Execution. With