

- Webapp – hostname
  - ~ - current directory
  - \$ - the prompt symbol
- If a command is in the root, it will look like
- `root@webapp:/var/log#`

## Customising on Windows terminal

The Linux terminal can be installed in Windows, and for this to be possible, we need the latest version of Windows installed in our system, after which we will be required to turn on the Windows Subsystem for Linux. Then simply follow the following commands.

Control-Panel->Programs->Turn Windows features on or off and mark the checkbox as on.

Once you have installed Ubuntu from the Windows store, you will be asked to create your credentials for the user. You can upgrade the packages or frameworks using the following command.

```
$ sudo apt-get update && sudo apt-get upgrade
```

You can access the Linux shell in the following commands

1. Go to the Windows Start menu.
2. Open Command Prompt and execute bash.
3. Open Linux shell here in the windows explorer.
4. Enter wsl in the address bar.

- Install Node.js
- `$ sudo apt-get install build-essential`
- `$ curl -o- https://raw.githubusercontent.com/nvm-sh/nvm/v0.34.0/install.sh | bash`
- `$ nvm install -lts`
- `source ~/.nvm/nvm.sh`

Restart Windows and install LAMP

- `$ sudo apt-get install lamp-server^`
- `# Start the MySQL service`
- `$ sudo service MySQL start`
- `# Define a password for root@localhost`
- `$ sudo MySQL`
- `mysql> ALTER USER 'root'@'localhost' IDENTIFIED WITH mysql_native_password BY 'password';`
- `exit`
- `Servername localhost`