

- **Bugs section:**

lists all limitations, and inconveniences with the use of this program.

- **Author section:**

informs the user about the name of the person and contact information, in case there are any errors or missing documentation.

- **See also section includes:**

a list of all related Man pages for the command or help in alphabetical order.

Location for Man Page

Ideally, man pages in Linux are found in either of the two directories:

- /usr/share/man
- /usr/local/man

You may find multiple subdirectories named man and number or a suffix representing a specific type of man page that may vary from system to system.

Most of these have the following numeric notation:

- 0 - header files
- 1 - standard commands
- 2 - Linux kernel system calls
- 3 - standard c library functions
- 4 - special devices
- 5 - file formats and conventions
- 6 - games and toys
- 7 - miscellaneous, for example, standards (for example SQL and ISO)
- 8 - root commands
- 9 - kernel details
- n - Tcl/Tk functionality

Sometimes there are special characters in the file names such as 'term.1tk' or 'ignore.1x'. These provide an indentation for a specific Tk application or an X Window program.

Working through Commands - Characteristics of Command

A Command is an instruction given to a computer program to perform specific tasks. It has to be in the form of one from these four different characteristics:

- Executable program: These are the binaries programs written in a language such as C, C++, Ruby, Perl, Python, shell, etc.
- Shell Builtins: Bash has several commands that are supported internally termed as shell builtins. Eg. cd command
- Shell function: Customised shell scripts added in the environment.