

represents that it can be used with either a -L or a -P, if -P is there, then -e can be used along with a 'dir' argument.

--help command for usage information

Several executable programs also support a --help option to provide more information for command options and syntax. Here is a simple demonstration of this fact.:

```
[me@linuxbox ~]$ mkdir --help
```

Usage: mkdir [OPTION] DIRECTORY...

Create the DIRECTORY(ies), if they do not already exist.

-Z, --context=CONTEXT (SELinux) set security context to CONTEXT-
Mandatory arguments to long options are mandatory for short options too.

-m, --mode=MODE set file mode (as in chmod), not a=rwx - umask

-p, --parents no error if existing, make parent directories as needed

-v, --verbose print a message for each created directory

--help display this help and exit

--version output version information and exit

man - Provide a program Manual page information

Most of the distribution package or programs for command-line interfaces comes with supported documentation termed as man page. Usually, there is a man program to call this display from the terminal. Syntax for man program:

- `man program`

Here, the program represents the name of the command. These Man pages are just for reference only and contain a title, synopsis, a description, a listing, and then a complete description of the options for the command. Here is a quick sample for displaying the man page of the ls command.

- `[me@linuxbox ~]$ man ls`

Man pages have several sections with the following layout.

SECTION	CONTENTS
1	User commands
2	Programming interfaces kernel system calls
3	Programming interfaces to the C library
4	Special files such as device nodes and drivers
5	File formats
6	Games and amusements such as screen savers
7	Miscellaneous
8	System administration commands