

- Users can view tar files. They can be recognised with traditional extensions such as “.tar.gz” or “.tgz”.

Commands

The commands mentioned below are the representation of filters which are programs used in pipelines. They take the standard input and perform a variety of tasks and finally send the results to the standard output. These commands can act as filters in several ways. Below you will find the common ones-

Uniq- can eliminate duplicate lines in the data and provide a sorted data stream through standard output. Example-

```
cat unsorted_list_with_dupes.txt | sort | uniq | pr
```

Wc- to filter results by isolating them in the main domain of the command. To count the order of the result, this command is used. Example-

- `$ grep .com domains | wc -l`

Grep- can analyse every line of the data stream which it receives from the standard output or input. Also, it can check if the line contains a specific pattern of the characters. Example-

- `$ grep GID / etc/ login.defs`

Head- the first few lines of the input are passed on. It is, however, not useful to get the header of the file. Example- to view the first line of file-

- `$ head -1 /etc/ password`

Tail- outputs the last few lines of the input, and it is useful to get the different countries in the directory from a log file. One can get to the lines of the text file. Example-

- `Tail/ etc/ profile`

Tee- copies the standard input of the file as well as output. It also saves the copy in a file named who.out and passes it to the standard output via pipeline.

- `$ who | tee who.out | grep sam`

Some important points-

- Every file has its corresponding file descriptor
- The keyboard is referred to as a standard input device and screen as the standard output device.
- Output redirection operator is ‘>’, and the input redirection operator is ‘<’.
- To redirect the output from one file to another, ‘>&’ symbol is used.
- Using the corresponding file descriptor ‘2’, one can redirect the error. 