

Here the interruptible processes are those that can be interrupted by the signals and continuous processes.

iii) Terminated /Zombie Process: These are dead processes that do not have any entry in the process table.

Several important commands of UNIX/Linux processes

There are several commands associated with any process. Here are some of the main commands associated with processes:

i) Starting a UNIX Process

You can start any foreground and background process just through the command line prompt. To start any background process, write the commands:

- `# cloudcmd &`
- `# jobs`

Through this command, all the commands that are running in the background will be displayed. Users can also send any process to run in the background by using `ctrl+z`. Through this command, a SIGSTOP signal is sent to the process, and it becomes idle. E,g shown in the following commands:

- `# tar -cf backup.tar /backups/* #press Ctrl+z`
- `# jobs`

If you want to run this program continuously in the background, then type “#bg” command. On the other hand, if you’re going to bring background process to the foreground, then you can use “#fg” command along with the job id.

ii) ps Command

To display the information of any active process on the system, we use this command. The syntax is given below:

- `# ps`
- `#ps -e: head`

Through this command the following output will be displayed:

PID	TTY	TIME	CMD
1	?	00:00:01	System
2	?	00:00:00	Kthreadadd
3	?	00:00:00	migration/0
4	?	00:00:00	rcuob/0
5	?	00:00:00	rcu_bh

iii) How to Send Signals to Processes