

To control any process, you can send signals to them. You can send multiple signals to the processes. To view all running processes, run the command:

- `$ kill -l`

The result of the above command will be like:

1) SIGSYS	2) SIGCONT	3) SIGIO	4) SIGPWR	5) SIGTSTP
6) SIGRTM	7) SIGKILL	8) SIGRTMAX	9) SIGQUIT	10) SIGUSR1
11) SIGSEGV	12) SIGABRT	13) SIGCHLD	14) SIGIO	15) SIGURG
16) SIGUSR2	17) SIGFPE	18) SIGILL	19) SIGTRAP	20) SIGBUS
21) SIGHUP	22) SIGCHLD	23) SIGXCPU	24) SIGTTIN	25) SIGTTOU

You can send the signal to a process by using commands `kill`, `pgrep` or `pkill`. Programs can only respond to signals. If the programs are recognized to identify the signals only, then they will react to them.

Most of the signals are only for internal use by the system. Usually, the following signals are used by the processes:

- SIGHUP 1- If the terminal is closed then the process sent this signal
- SIGINT 2 - If any user interrupts the process through the `ctrl+c` key, then this signal is sent to the process by its controlling terminal.
- SIGKILL 9 - To immediately terminate or kill any process this signal is being sent to any process. The process will not perform any clean-up operation.
- SIGQUIT 3 - If any user send a quit signal by pressing `ctrl+D` then this signal is being sent to the process
- SIGTSTP 20 - the controlling terminal sends this signal to the process to request the process to stop its operation, that s initialized by the user by pressing `ctrl + z`

Users can kill a process either through its name or process ID. If you want to kill it by name, then you can use the `pkill` command else `killall`. Like to kill “firefox” process, we can use the following commands:

- `$ pkill firefox`
- `$ killall firefox`

iv) How to Change Linux Process Priority?

All processes of the Linux operating system have some priority and a particular nice value. The processes that have high priority value get more CPU time rather than those having low priority value.

The system user with root privileges can change it with `nice` and `renice` commands. You can see the nice value of the processes by using `top` command. An example is shown below:

- `$ top`